

DATA SHEET

POSITIVE TEMPERATURE COEFFICIENT AC/DC POWER SUPPLY

BKH32 Series

RoHS compliant



Product specification— April 28, 2025 V.2



Positive Temperature Coefficient (PTC) Data Sheet

Description

The BKH32 series provides radial resettable overcurrent protection with holding current from 0.5A to 10A. This series is suitable for applications with higher working voltage up to 32V.




Features


- Low resistance
- Fast response to fault current
- Compatible with high-volume electronics assembly
- High Operation Temperature - -40°C ~ 125°C
- Resettable solution against overcurrent and short-circuit
- RoHS compliant (Lead Free)

Applications

- Actuators and medium motors
- Industrial power supply
- Automotive ECU and current sensor etc. protection
- Industrial motor driver
- Powered outputs
- Harness/junction box protection

Part Number Code and Marking





Dimensions and PAD-SIZE(Unit: mm)




Fig.1




Fig.2




Fig.3

Part Number	Figure	A Max.	B Max.	C Typ.	D Min.	E Typ.	F Min.
BKH32-050	3	7.4	12.7	5.1	3.3	0.51	7.6
BKH32-070	2	6.9	10.8	5.1	3.0	0.51	7.6
BKH32-100	3	9.7	13.6	5.1	3.0	0.51	7.6
BKH32-200	1	9.5	13.5	5.1	3.0	0.81	7.6
BKH32-300	1	10.2	15.5	5.1	3.8	0.81	7.6
BKH32-500	1	14.0	24.1	5.1	3.8	0.81	7.6
BKH32-750	1	21.1	24.9	10.2	3.8	0.81	7.6
BKH32-1000	1	23.5	27.9	10.2	4.0	1.00	7.6

Electrical Characteristics

Part Number	I_{hold} (A)	I_{trip} (A)	V_{max} (V _{DC})	I_{max} (A)	$P_{d\ typ.}$ (W)	Maximum Time To Trip		Resistance	
						Time (Sec.)	Current (A)	R_{min} (Ω)	R_{1max} (Ω)
BKH32-050	0.5	1.0	32	100	0.9	3.0	2.5	0.35	1.10
BKH32-070	0.7	1.4	32	100	1.4	3.2	3.5	0.23	0.80
BKH32-100	1.0	2.0	32	100	1.4	6.2	5.0	0.15	0.43
BKH32-200	2.0	4.0	32	100	2.2	5.5	10.0	0.065	0.250
BKH32-300	3.0	6.0	32	100	3.2	5.0	15.0	0.035	0.110
BKH32-500	5.0	10.0	32	100	5.3	9.0	25.0	0.015	0.040
BKH32-750	7.5	15.0	32	100	6.5	13.0	37.5	0.0074	0.0230
BKH32-1000	10.0	20.0	32	100	7.0	15.0	50.0	0.0060	0.0160

Note on Electrical Characteristics

■ Vocabulary

- I_{hold} = Hold current: maximum current device will pass without tripping in 23°C still air.
- I_{trip} = Trip current: minimum current at which the device will trip in 23°C still air.
- V_{max} = Maximum voltage device can withstand without damage at rated current (I_{max})
- I_{max} = Maximum fault current device can withstand without damage at rated voltage (V_{max})
- $P_{d\ typ.}$ = Typical power dissipated from device when in the tripped state at 23°C still air.
- R_{min} = Minimum resistance of device in initial (un-soldered) state.
- R_{1max} = Maximum device resistance at 23°C, 1 hour after tripping.

■ Caution: Operation beyond the specified rating may result in damage and possible arcing and flame.

Polymeric PTC Selecting Guide

■ Determine the following operating parameters for the circuits:

- Normal operating current (I_{hold})
- Maximum interrupt current (I_{max})
- Maximum circuit voltage (V_{max})
- Normal operating temperature surrounding device (min°C/max°C)

■ Select the device from factor and dimension suitable for the application

■ Compare the maximum rating for V_{max} and I_{max} of the PPTC device with the circuit in application and make sure the circuit's requirement does not exceed the device rating.

■ Check that PPTC device's trip time (time-to-trip) will protect the circuit.

■ Verify that the circuit operating temperature is within the PPTC device's normal operating temperature range.

■ Verify that performance and suitability of the chosen PPTC device in the application.

 WARNING**■ Mechanical Stress**

- PPTC devices will undergo a thermal expansion during fault condition. If PPTC devices are installed or placed in an application where the space between PPTC devices and the surrounding materials (e.g., covering materials, packaging materials, encapsulate materials and the like) is insufficient, it will cause an inhibiting effect upon the thermal expansion. Pressing, twisting, bending and other kinds of mechanical stress will also adversely affect the performance of the PPTC devices, and shall not be used or applied.

■ Chemical Pollutants

- Silicone-based oils, oils, solvents, gels, electrolytes, fuels, acids, and the like will adversely affect the properties of PPTC devices, and shall not be used or applied.


■ Electronic and Thermal Effect

- PPTC devices are secondary protection devices and are used solely for sporadic, accidental over-current or over-temperature error condition, and shall NOT be used if or when constant or repeated fault conditions (such fault conditions may be caused by, among others, incorrect pin-connection of a connector) or over-extensive trip events may occur.
- PPTC devices are different from fuses and, when a fault condition occurs, will go into high-resistance state and do not open circuit, in which case the voltage at such PPTC devices may reach a hazardous level.
- Operation over the maximum rating or other forms of improper use may cause failure, arcing, flame and/or other damage to the PPTC devices.
- Conductive material contamination, such as metal particle, may induce shortage, flame or arcing.
- Due to the inductance, the operation circuits may generate a circuit voltage (Ldi/dt) above the rated voltage of PPTC devices, which shall not be used under such circumstances.

■ General

- Customers shall evaluate and test the properties of PPTC devices independently to verify and ensure that their individual applications will be met.
- The performance of PPTC devices will be adversely affected if they are improperly used under electronic, thermal and/or mechanical procedures and/or conditions non-conformant to those recommended by manufacturer.
- Customers shall be responsible for determining whether it is necessary to have back-up, failsafe and/or fool-proof protection To avoid or minimize damage that may result from extra-ordinary, irregular function or failure of PPTC devices.
- Any and all responsibilities and liabilities are disclaimed if any item under this notice of warning is not complied with.

Thermal Derating Curve



Thermal Derating Chart – I_H (A)

Recommended Hold Current (A) at Ambient Temperature (°C)


Part Number	Maximum Ambient Operating Temperatures (°C)									
	-40°C	-20°C	0°C	23°C	40°C	50°C	60°C	70°C	85°C	125°C
BKH32-050	0.72	0.65	0.58	0.50	0.44	0.40	0.36	0.33	0.28	0.14
BKH32-070	1.00	0.91	0.81	0.70	0.62	0.56	0.50	0.46	0.39	0.20
BKH32-100	1.43	1.30	1.15	1.0	0.88	0.80	0.72	0.65	0.55	0.28
BKH32-200	2.86	2.60	2.30	2.0	1.76	1.60	1.44	1.30	1.10	0.56
BKH32-300	4.29	3.90	3.45	3.0	2.64	2.40	2.16	1.95	1.65	0.84
BKH32-500	7.15	6.50	5.75	5.0	4.40	4.00	3.60	3.25	2.75	1.40
BKH32-750	10.73	9.75	8.63	7.50	6.60	6.00	5.40	4.88	4.13	2.10
BKH32-1000	14.30	13.00	11.50	10.0	8.80	8.00	7.20	6.50	5.50	2.80

Test Procedures and Requirement

Items	Test Conditions	Accept/Reject Criteria
Resistance	In still air @25°C	$R_{min} \leq R \leq R_{max}$
Time to Trip	Specified current, V_{max} , 25°C	$T \leq \text{max. Time to trip } (T_{trip})$
Hold Current	30 min, at I_H	No trip
Trip Cycle Life	V_{max} , I_{max} , 100 cycles	No arcing or burning
Trip Endurance	V_{max} , 24hours	No arcing or burning

Typical Time-to-Trip Charts at 23°C


A= BKH32-050
 B= BKH32-070
 C= BKH32-100
 D= BKH32-200
 E= BKH32-300
 F= BKH32-500
 G= BKH32-750
 H= BKH32-1000



Storage Recommendations

- Storage Temperature: -10°C~+40°C
- Relative Humidity: ≤80%RH
- Keep away from corrosive atmosphere and sunlight.
- Period of Storage: 1 year.

Wave Soldering Recommendation Parameters



Items	Conditions
Pre-Heating Zone	Refer to the condition recommended by the flux manufacturer. Maximum ramping rate should not exceed 4°C/sec.
Soldering Zone	Maximum solder temperature should not exceed 260°C
Cooling Zone	Forced cooling

Manual Soldering Recommendation Parameters

Items	Conditions
Soldering condition	The highest power of the manual soldering iron should be 30W or less, soldering temperature should not be higher than 280°C.
Soldering time	The soldering time should be kept within 3 seconds, otherwise it might cause insulation layer cracking, and increased part resistance.
Soldering position	The distance on the leads between the soldering point and bottom of the PPTC body should be equal or greater than 4mm.
Other	The soldering iron should not contact the PPTC body except the leads. If the soldering conditions are kept to lower temperature, less time and larger distance, the outcome of the soldering will be better.

Mechanical Characteristics


Items	Specifications	Test Conditions/Methods
Tensile strength	No visible damage	1.0Kgf, 10 seconds
Bending strength	No visible damage	0.5Kgf, 90° , 3 times
Vibration	No visible damage	Freq: 10-55Hz, Amp: 0.75mm, 1min

Reliability Test

Items	Specifications	Test Conditions/Methods
Solder ability	No visible damage, Solder OK, Solder area ≥95%	245±5°C, 5+0/-0.5s, dipping depth=0.5inch max from the body
Resistance to soldering heat	No visible damage, Electrical OK	260±5°C, 20±1s
Damp heat, steady state	No visible damage, Electrical OK, $ \Delta R/R_0 \leq 25\%$	85±5°C, 85±5 % RH, total 24Hrs, after 4Hrs test electrical parameter
Temperature cycling	Electrical OK, No cracking, breaks, bond lifting, etc.	Ta=-40°C/30min, Ta=125°C/30min, Unpowered, 1000cycles, after 24hr test electrical parameter

Packaging

Part Number	PCS/BAG	Reel/Tape	Part Number	PCS/BAG	Reel/Tape
BKH32-050	500	2500	BKH32-300	200	1500
BKH32-070	500	2500	BKH32-500	200	---
BKH32-100	300	1500	BKH32-750	100	---
BKH32-200	300	1500	BKH32-1000	100	---



LEGAL DISCLAIMER

YAGEO, its distributors and agents (collectively, "YAGEO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non -infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment, Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly **YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.**

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.