



Click [here](#) for the 3D model.

General Information

| | |
|-------------------------|--|
| Series | GR900 SMD Space BX |
| Style | SMD Chip |
| RoHS | No |
| Prop 65 | WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov/ |
| SCIP Number | 2a1e1a41-ed35-45dd-8d0d-907fc06efdab |
| Termination | Lead (SnPb) |
| Failure Rate | N/A |
| Testing and Reliability | GR900 CSAM A |
| Shelf Life | 78 Weeks |
| MSL | 1 |

Specifications

| | |
|-------------------|------------|
| Capacitance | 0.047 uF |
| Tolerance | 10% |
| Voltage DC | 50 VDC |
| Temperature Range | -55/+125°C |
| Temp. Coefficient | BX |

Dimensions

| | |
|----------------------|------------------|
| L | 3.07mm +/-0.38mm |
| W | 1.52mm +/-0.38mm |
| T | 1.6mm MAX |
| B | 0.51mm +/-0.25mm |
| Case Code (EIA / mm) | 1206 / 3216 |

Packaging Specifications

| | |
|-----------|-------------------|
| Packaging | T&R, Plastic Tape |
|-----------|-------------------|

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.