
C4AEGBU4680A1XJ

Not for New Design

C4AE, Film, Metallized Polypropylene, DC Link, 6.8 uF, 5%, 450 VDC, 85°C, 27.5 mm



Click here for the 3D model.

General Information	
Series	C4AE
Dielectric	Metallized Polypropylene
Style	Radial
RoHS	Yes
Termination	Tin
Lead	Wire Leads
Typical Component Weight	16 g
Miscellaneous	Thermal Resistance = 36 C/W.
Notes	Not for new design – the replacement series is: C4AQ.

Dimensions	
L	31.5mm +0.5/-0.7mm
H	25mm +0.2/-0.7mm
T	13mm +0.3/-0.7mm
S	27.5mm +/-0.4mm
LL	6mm -2mm
F	0.8mm NOM
G	0.5mm NOM

Packaging Specifications	
Packaging	Bulk, Box

Specifications	
Capacitance	6.8 uF
Tolerance	5%
Voltage DC	450 VDC
Temperature Range	-40/+85°C
Rated Temperature	85°C
Insulation Resistance	4.41 GOhms
Max dV/dt	15 V/us
ESR	10 mOhms (10kHz 70C)
Ripple Current	6 Amps (10kHz 70C), 101 Amps (Peak)
Inductance	25 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

© 2006 - 2026 YAGEO