



Click [here](#) for the 3D model.

**General Information**

|                          |   |
|--------------------------|---|
| Series                   | SMR/F211  |
| Dielectric               | Metallized PPS  |
| Style                    | Radial  |
| Features                 | Audio Applications  |
| RoHS                     | Yes   |
| Termination              | Tinned Wire   |
| Lead                     | Wire Leads  |
| Typical Component Weight | 0.5 g   |
| Miscellaneous            | The rated voltage decreases 2%/C between +125C and +150C. |
| Notes                    | Case Size = KG.   |

**Specifications**

|                       |                                      |
|-----------------------|--------------------------------------|
| Capacitance           | 0.01 uF                              |
| Tolerance             | 5%                                   |
| Voltage DC            | 63 VDC                               |
| Voltage AC            | 40 VAC                               |
| Temperature Range     | -55/+150°C                           |
| Rated Temperature     | 125°C                                |
| Dissipation Factor    | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
| Insulation Resistance | 15 GOhms                             |
| Max dV/dt             | 30 V/us                              |

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|

|                   |       |
|-------------------|-------|
| Rated Temperature | 125°C |
|-------------------|-------|

|                    |                                      |
|--------------------|--------------------------------------|
| Dissipation Factor | 0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz |
|--------------------|--------------------------------------|

|                       |          |
|-----------------------|----------|
| Insulation Resistance | 15 GOhms |
|-----------------------|----------|

|           |         |
|-----------|---------|
| Max dV/dt | 30 V/us |
|-----------|---------|

|             |         |
|-------------|---------|
| Capacitance | 0.01 uF |
|-------------|---------|

|           |    |
|-----------|----|
| Tolerance | 5% |
|-----------|----|

|            |        |
|------------|--------|
| Voltage DC | 63 VDC |
|------------|--------|

|            |        |
|------------|--------|
| Voltage AC | 40 VAC |
|------------|--------|

|                   |            |
|-------------------|------------|
| Temperature Range | -55/+150°C |
|-------------------|------------|